

EN

Electrohydraulic tyre changer for rim sizes up to 26" for demounting and mounting tyres with or without inner tubes for trucks, buses and industrial vehicles.
Manual arm lifting and tool tipping.

IT

Smontagomme elettroidraulico per ruote fino a 26" per lo smontaggio e montaggio di pneumatici con o senza camera d'aria per autocarri, bus e veicoli industriali.
Alzata braccio e ribaltamento utensile manuale.

DE

Elektrohydraulische Reifenmontiermaschine für Räder bis 26" zur Demontage und Montage von Reifen mit oder ohne Luftschlauch für Lkws, Busse und Nutzfahrzeuge.
Heben des Arms und Kippen des Werkzeugs manuell.


FIT LINE 53

EN → Standard IT → Dotazione DE → Standardzubehör

PC
cod. 219244H



LC
cod. 801417620



LA
cod. 801217615



EN → Recommended accessories IT → Accessori consigliati DE → Empfohlenes Zubehör



PL
cod. 8011227195



ACL

8-12100007 = Ø 161 mm
8-12100005 = Ø 164 mm
8-12100006 = Ø 176 mm
8-12100008 = Ø 202 mm
8-12300001 = Ø 220 mm
8-12100009 = Ø 221 mm
8-12100010 = Ø 281 mm

EN → • PL Alloy rim clamp tool. • ACL Locking adapter for alloy wheels

IT → • PL Pinza per cerchi in lega. • ACL Adattatore bloccaggio cerchi in lega

DE → • PL Wulsthalter für Leichtmetallräder • ACL Radadapter für Alu-Felgen

EN → Technical Data IT → Dati Tecnici DE → Technische Daten

Power supply	Alimentazione elettrica	Versorgungsspannung	400V - 3ph - 50/60Hz 230V - 3ph - 60Hz 230V - 1ph - 50/60Hz
Chuck clamping capacity	Capacità di presa autocentrante	Aufnahmebereich Spannteller	14" - 26"
Max. wheel diameter	Diametro massimo ruota	Maximaler Raddurchmesser	1500 mm
Max. wheel width	Larghezza massima ruota	Maximale Radbreite	780 mm
Bead breaking force:	Forza di stallonamento:	Abdrückkraft	16000 N
Max. torque delivery	Coppia massima fornita	Einspannkraft Spannteller	41000 N
Max weight of wheel	Peso massimo della ruota	Max. Radgewicht	700 kg
Minimal diameter of the center hole of rim	Diametro minimo del foro centrale del cerchione	Max. geliefertes Drehmoment	120 mm
Working pressure	Pressione d'esercizio	Betriebsdruck	130 bar
Chuck rotation speed	Velocità rotaz. autocentrante	Drehgeschw. Spannteller	6 r.p.m.
Motor power	Potenza motore	Motorleistung	1.5 kW (oil) 1.8 kW (gearbox)
Weight machine	Peso macchina	Maschinengewicht	498 kg

The manufacturer reserves the right to modify the features of its products at any time. Fotografie, caratteristiche ed i dati tecnici non sono vincolanti, possono subire modifiche senza preavviso. Die Fotografien, die angegebenen Eigenschaften und die technischen Daten sind nicht verbindlich und können ohne Vorankündigung geändert werden.



SICE
AUTOMOTIVE EQUIPMENT

NEXION SPA - ITALY -

www.sice.it - sice@sice.it

